

Attorney Docket No. P11258

LISTING OF CLAIMS

1. (Currently Amended) A method for of controlling a data unit oriented communication between a sender and a receiver operating in accordance with a predetermined communication protocol, said method comprising the steps of:

dividing, by the sender, [[of]] an amount of data to be sent into at least one data unit a plurality of data units having a structure determined by the protocol;

transmitting initial data units from the sender to the receiver;

acknowledging, by the receiver, [[of]] correct receipt of the initial data units by returning acknowledgment data units to the sender;

detecting a failure of the receiver to receive at least one data unit;

retransmitting, by the sender, the at least one data unit that the receiver failed to receive;

receiving at the sender, an acknowledgment data unit indicating that at least one of the data units was correctly received by the receiver;

determining whether the received acknowledgment data unit indicates that one of the correctly received data units was correctly received as a result of the transmitting step or as a result of the retransmitting step;

sending subsequently transmitting, by the sender, of the subsequent data units, said subsequent data units being transmitted in accordance with a flow control procedure conducted on the basis of at least one adaptive parameter and the acknowledgment data units, said subsequently transmitting step including:

performing an excessive delay response procedure upon determining that the received acknowledgment data unit indicates that the at least one data unit was correctly received as a result of the transmitting step; and

performing a data unit loss response procedure upon determining that the received acknowledgment data unit indicates that the at least one data unit was correctly received as a result of the retransmitting step.

wherein the flow control procedure comprises a data loss detection mechanism capable of detecting data loss in the communication;

S - R
Ack

No Ack
↓
failure
retransmit
Ack

Ack via
transmit or
retransmit

Timeout

congestion

PT 1119-
Thurs 11/19/03

works on retransmission

Attorney Docket No. P11258

~~wherein the data loss detection mechanism is triggered to indicate the potential loss of data by at least one predetermined event;~~

~~wherein, in response to the triggering of the data loss detection mechanism, a corresponding response procedure is conducted; and~~

~~wherein the response procedure comprises at least two different modes for adapting the at least one adaptive parameter.~~

B? *OK Cont.*
2. (Currently Amended) The method of claim 1, wherein the step of detecting a failure of the receiver to receive at least one data unit includes the steps of:

~~the data loss detection mechanism comprises a time out mechanism after a data unit is sent, the sender monitors~~ monitoring a time out period by the sender after the at least one data unit is sent, and;

~~if no acknowledgment data unit associated with the data unit is received before the time out period expires, triggering a the time out mechanism is triggered that indicates the failure.~~

3. (Currently Amended) The method of claim 1, wherein the step of detecting a failure of the receiver to receive at least one data unit includes the steps of:

~~the data loss detection mechanism comprises a duplicate acknowledgment detection mechanism;~~

~~the sender monitors the received acknowledgments, and;~~

~~determining by the sender whether duplicate acknowledgment data units are received for a transmitted data unit; and~~

~~if a data unit is acknowledged a predetermined number of times, the triggering a duplicate acknowledgment detection mechanism is triggered that indicates the failure.~~

4-5. (Canceled)

6. (Currently Amended) The method of claim 2, wherein the time out period comprises is one of the adaptive parameters in the flow control procedure.

Attorney Docket No. P11258

7. (Currently Amended) The method of claim 1, wherein the flow control procedure is window-based, and at least one flow control window is among the adaptive parameters in the flow control procedure.

8. (Canceled)

9. (Currently Amended) The method of claim ~~[[8]]~~ 1, wherein the step of determining whether the received acknowledgment data unit indicates that the at least one data unit was correctly received as a result of the transmitting step or as a result of the retransmitting step includes the steps of:

the sender marks marking the initial data units being sent by the sender such that an original transmission can be distinguished from a retransmission; and

the receiver correspondingly marks marking the acknowledgment data units by the receiver, such that ~~the~~ an acknowledgment data unit associated with ~~[[of]]~~ an originally sent initial data unit can be distinguished from the an acknowledgment data unit associated with a retransmitted ~~of the retransmission of the data unit~~.

10. (Currently Amended) The method of claim 9, wherein:

the step of marking the initial data units by the sender marks data units by includes the step of including a time stamp in each sent initial data unit, the time stamp indicating the time the data unit was sent; and

the step of marking the acknowledgment data units by the receiver marks the acknowledgment data unit for a received data unit by includes the step of including the time stamp contained in the received a given initial data unit in the acknowledgment data unit for the received associated with the given initial data unit.

11. (Currently Amended) The method of claim 9, wherein:

the step of marking the initial data units by the sender marks data units by includes the step of including a bit string in each sent initial data unit, the bit string having at least two different values for distinguishing between an original transmission and a retransmission; and

Attorney Docket No. P11258

the step of marking the acknowledgment data units by the receiver marks the acknowledgment data unit for a received data unit by includes the step of including the bit string contained in the received a particular initial data unit in the acknowledgment data unit for the received associated with the particular initial data unit.

12. (Previously Presented) The method of claim 11, wherein the bit string consists of a single bit.

13. (Previously Presented) The method of claim 11, wherein the bit string consists of a plurality of bits, such that the bit string is capable of distinguishing between different retransmissions.

14. (Canceled)

15. (Currently Amended) The method of claim [[8]] 2, wherein the step of determining whether the received acknowledgment data unit indicates that the at least one data unit was correctly received as a result of the transmitting step or as a result of the retransmitting step includes the steps of:

determining by the sender, measures the a shortest round trip time associated with the connection for sending of the amount of data correct receipt of an initial data unit;

measuring by the sender, a the time period between the retransmission of the a given data unit and the receipt of the a first acknowledgment data unit associated with the given data unit is determined and;

compared to a value derived from at least one of the round trip time measurements; and

the first or second mode is chosen on the basis of the result of the comparison comparing the shortest round trip time to the time period between the retransmission of the given data unit and the receipt of the first acknowledgment data unit; and

Attorney Docket No. P11258

determining that the at least one data unit was correctly received as a result of the transmitting step if the time period between the retransmission of the given data unit and the receipt of the first acknowledgment data unit is shorter than a predetermined fraction of the shortest round trip.

16. (Canceled)

B p cont.
17. (Currently Amended) The method of claim [[8]] 2, wherein the ~~second mode comprises~~ step of performing an excessive delay response procedure includes adapting the time out period on the basis of the a time period measured that elapsed between the original transmission of the transmitting a given data unit and receipt of the a first acknowledgment data unit associated with the given data unit.

18. (Currently Amended) The method of claim [[8]] 2, wherein the flow control procedure for retransmitting the at least one data unit is window-based, and a congestion window is used[[;]], and the method further comprises the steps of:

storing the value of the congestion window upon detecting the failure of the receiver to receive the at least one data unit; at the time of the triggering event is stored after the triggering event occurred and

subsequently resetting the value of the congestion window is reset to a predetermined value; and

upon performing the excessive delay response procedure, if the second mode is chosen after having received the first acknowledgment data unit associated with the given data unit, setting the value of the congestion window is set to the value it would have assumed, had the excessive delay response procedure not taken place.

19-34. (Canceled)

Attorney Docket No. P11258

35. (New) A device for controlling a data unit oriented communication between a sender and a receiver operating in accordance with a predetermined communication protocol, said device comprising:

means in the sender for dividing an amount of data to be sent into a plurality of data units having a structure determined by the protocol;

a data unit transmitter that transmits the data units from the sender to the receiver;

means in the receiver for acknowledging correct receipt of the transmitted data units by returning acknowledgment data units to the sender;

a data loss detection mechanism that detects a failure of the receiver to receive at least one data unit;

retransmission means in the sender that retransmits the at least one data unit that the receiver failed to receive;

receiving means in the sender for subsequently receiving an acknowledgment data unit indicating that the at least one data unit was correctly received by the receiver;

determining means for determining whether the received acknowledgment data unit indicates that the at least one data unit was correctly received as a result of the transmitting step or as a result of the retransmitting step;

means within the transmission means for subsequently transmitting subsequent data units utilizing a flow control procedure conducted on the basis of at least one adaptive parameter, said subsequent transmission means including:

an excessive delay response mechanism that performs an excessive delay response procedure in response to the determining means determining that the received acknowledgment data unit indicates that the at least one data unit was correctly received as a result of the transmitting step; and

a data unit loss response mechanism that performs a data unit loss response procedure in response to the determining means determining that the received acknowledgment data unit indicates that the at least one data unit was correctly received as a result of the retransmitting step.

Attorney Docket No. P11258

36. (New) The device of claim 35, wherein the data loss detection mechanism includes:

a first timer in the sender for monitoring a time out period after the at least one data unit is sent, and;

a time out mechanism that indicates the failure of the receiver to receive the at least one data unit, said time out mechanism being triggered if no acknowledgment data unit associated with the data unit is received before the time out period expires.

Bp 12/1/03
37. (New) The device of claim 35, wherein the data loss detection mechanism includes a duplicate acknowledgment detection mechanism in the sender that detects whether a predetermined number of duplicate acknowledgment data units are received for a transmitted data unit.

38. (New) The device of claim 36, wherein the time out period is one of the adaptive parameters in the flow control procedure.

39. (New) The device of claim 35, wherein the retransmission means includes a window-based flow control procedure, and at least one flow control window is among the adaptive parameters in the flow control procedure.

40. (New) The device of claim 35, wherein the determining means includes:
marking means in the sender for marking the transmitted data units such that an original transmission can be distinguished from a retransmission; and

marking means in the receiver for marking the acknowledgment data units such that an acknowledgment data unit associated with an originally sent data unit can be distinguished from an acknowledgment data unit associated with a retransmitted data unit.

Attorney Docket No. P11258

41. (New) The device of claim 40, wherein:

the marking means in the sender includes a first time stamp mechanism that places a time stamp in each transmitted data unit, the time stamp indicating the time the data unit was sent; and

the marking means in the receiver includes a second time stamp mechanism that places the time stamp contained in a given transmitted data unit in the acknowledgment data unit associated with the given transmitted data unit.

42. (New) The device of claim 40, wherein:

the marking means in the sender places a bit string in each transmitted data unit, the bit string having at least two different values for distinguishing between an original transmission and a retransmission; and

the marking means in the receiver places the bit string contained in a particular transmitted data unit in the acknowledgment data unit associated with the particular transmitted data unit.

43. (New) The device of claim 42, wherein the bit string consists of a single bit.

44. (New) The device of claim 42, wherein the bit string consists of a plurality of bits, such that the bit string is capable of distinguishing between different retransmissions.

45. (New) The device of claim 35, wherein the determining means includes:

a first timer in the sender that measures a shortest round trip time associated with the correct receipt of a transmitted data unit;

a second timer in the sender that measures a time period between the retransmission of a given data unit and the receipt of a first acknowledgment data unit associated with the given data unit;

Attorney Docket No. P11258

means for comparing the shortest round trip time to the time period between the retransmission of the given data unit and the receipt of the first acknowledgment data unit; and

means for determining that the at least one data unit was correctly received as a result of the transmitting step if the time period between the retransmission of the given data unit and the receipt of the first acknowledgment data unit is shorter than a predetermined fraction of the shortest round trip.

46. (New) The device of claim 36, wherein the excessive delay response mechanism includes means for adapting the time out period on the basis of a time period measured between transmitting a given data unit and receipt of a first acknowledgment data unit associated with the given data unit.

47. (New) The device of claim 36, wherein the subsequent transmission means includes a windows-based flow control procedure that utilizes a congestion window, and the device further comprises:

storage means for storing the value of the congestion window when the data loss detection mechanism detects the failure of the receiver to receive the at least one data unit;

means for subsequently resetting the value of the congestion window to a predetermined value; and

means for setting the value of the congestion window, after the excessive delay response mechanism performs the excessive delay response procedure, to a value that the congestion window would have assumed, had the excessive delay response procedure not taken place.

Attorney Docket No. P11258

48. (New) An improved method of controlling a data unit oriented communication between a sender and a receiver operating in accordance with a predetermined communication protocol, wherein the sender divides an amount of data into one or more data units having a structure determined by the protocol; the receiver acknowledges correct receipt of data units by returning acknowledgment data units to the sender; and the sender sends the data units to the receiver in accordance with a flow control procedure conducted on the basis of one or more adaptive parameters and the acknowledgment data units, the flow control procedure including a data loss detection procedure that, responsive to one or more triggering events, indicates potential data loss in the communication, and a response procedure in which a given data unit is re-sent from the sender to the receiver, wherein the improvement comprises:

selecting by the response procedure, a mode for adapting the one or more adaptive parameters of the flow control procedure, said mode being selected from at least two different modes, and being selected based on one or more acknowledgment data units received by the sender after having re-sent the given data unit.

49. (New) The method of claim 48, wherein the selecting step includes the steps of:

determining whether the received acknowledgment data units indicate that at least one data unit was correctly received as a result of being re-sent from the sender to the receiver;

selecting a mode for adapting the adaptive parameters to perform an excessive delay response procedure upon determining that it is not a result of being re-sent that the at least one data unit was correctly received; and

selecting a mode for adapting the adaptive parameters to perform a data unit loss response procedure upon determining that the at least one data unit was correctly received as a result of being re-sent.